

# DEVELON

Europe

## Full liner



# MINI EXCAVATORS



DX10Z-7



DX17Z-7

|                       |                |                  |                  |
|-----------------------|----------------|------------------|------------------|
| Operating weight      | kg             | 1165             | 1850             |
| Engine power          | hp/kW @ rpm    | 10.33/7.4 @ 2050 | 16.5/11.9 @ 2400 |
| Bucket capacity (SAE) | m <sup>3</sup> | 0.024            | 0.04             |
| Battery capacity      | kW             | -                | -                |
| Charging time         | -              | -                | -                |



DX25Z-7



DX27Z-7



DX35Z-7

|  |                   |                  |                  |
|--|-------------------|------------------|------------------|
|  | 2691              | 2730             | 3499             |
|  | 24.8 /18.5 @ 2600 | 24.8/18.5 @ 2400 | 24.8/18.4 @ 2400 |
|  | 0.07              | 0.08             | 0.11             |

|                       |                | DX10Z-7          | DX17Z-7          | DX19-7           | DX20Z             |
|-----------------------|----------------|------------------|------------------|------------------|-------------------|
| Operating weight      | kg             | 1165             | 1850             | 1885             | 1995              |
| Bucket capacity (SAE) | m <sup>3</sup> | 0.024            | 0.04             | 0.04             | 0.05              |
| Battery capacity      | kW             | -                | -                | -                | -                 |
| Charging time         | -              | -                | -                | -                | -                 |
| Travel speed          | km/h           | 3.4 - 1.7        | 2.21 - 4.09      | 2.06 - 3.73      | -                 |
| Engine model          | -              | Kubota D722      | Kubota D902      | Kubota D902      | Yanmar 3TNV70     |
| Power                 | hp/kW @ rpm    | 10.33/7.4 @ 2050 | 16.5/11.9 @ 2400 | 16.5/11.9 @ 2400 | 13.8 /10.3 @ 2200 |
| Emission standard     | -              | Stage V          | Stage V          | Stage V          | Stage V           |
| Digging reach         | mm             | 3400             | 3910             | 3940             | 3975              |
| Digging depth         | mm             | 1815             | 2240             | 2340             | 2345              |
| Digging height        | mm             | 2205             | 3730             | 3470             | 2750              |
| Length                | mm             | 3010             | 3531             | 3837             | 3483              |
| Width                 | mm             | 1100 (730)       | 1290 (994)       | 1290 (994)       | 1360 (950)        |
| Height                | mm             | 2220             | 2320             | 2299             | 2360              |



**DX19-7**



**DX20Z**



**DX20ZE**

|                  |                   |                                            |
|------------------|-------------------|--------------------------------------------|
| 1885             | 1995              | 1941                                       |
| 16.5/11.9 @ 2400 | 13.8 /10.3 @ 2200 | -                                          |
| 0.04             | 0.05              | 0.05                                       |
| -                | -                 | 20.4 kW                                    |
| -                | -                 | 8 hrs slow charger<br>1.5 hrs fast charger |



**DX50Z-7**



**DX55R-7**

|                  |                  |
|------------------|------------------|
| 5438             | 5740             |
| 48.8/36.4 @ 2200 | 48.8/36.4 @ 2200 |
| 0.16             | 0.16             |

| DX20ZE                                     | DX25Z-7          | DX27Z-7          | DX35Z-7          | DX50Z-7          | DX55R-7          |
|--------------------------------------------|------------------|------------------|------------------|------------------|------------------|
| 1941                                       | 2691             | 2730             | 3499             | 5438             | 5740             |
| 0.05                                       | 0.07             | 0.08             | 0.11             | 0.16             | 0.16             |
| 20.4 kW                                    | -                | -                | -                | -                | -                |
| 8 hrs slow charger<br>1.5 hrs fast charger | -                | -                | -                | -                | -                |
| -                                          | -                | 2.5 - 4.3        | 2.6 - 4.7        | 2.6 - 4.4        | 2.6 - 4.4        |
| -                                          | Kubota D1305     | Kubota V1505     | Develon D17      | Develon D18      | Develon D18      |
| -                                          | 24.8/18.5 @ 2600 | 24.8/18.5 @ 2400 | 24.8/18.4 @ 2400 | 48.8/36.4 @ 2200 | 48.8/36.4 @ 2200 |
| -                                          | Stage V          | Stage V          | Stage V          | Stage V          | Stage V          |
| 3975                                       | 4725             | 4845             | 5355             | 5945             | 6090             |
| 2350                                       | 2690             | 2845             | 3275             | 3480             | 3630             |
| 2625                                       | 4290             | 4515             | 3580             | 5575             | 5680             |
| 3460                                       | 4170             | 4190             | 4760             | 5386             | 5400             |
| 1360 (950)                                 | 1554             | 1550             | 1700             | 1980             | 1980             |
| 2345                                       | 2452             | 2442             | 2479             | 2575             | 2575             |

# MINI EXCAVATORS

|                       |                |
|-----------------------|----------------|
| Operating weight      | kg             |
| Engine power          | hp/kW<br>@ rpm |
| Bucket capacity (SAE) | m <sup>3</sup> |



## DX63-7

|                       |                |                |
|-----------------------|----------------|----------------|
| Operating weight      | kg             | 6218           |
| Engine power          | hp/kW @ rpm    | 65/44.3 @ 2300 |
| Bucket capacity (SAE) | m <sup>3</sup> | 0.175          |

## DX62R-7

|                       |                |                   |
|-----------------------|----------------|-------------------|
| Operating weight      | kg             | 6216              |
| Bucket capacity (SAE) | m <sup>3</sup> | 0.175             |
| Travel speed          | km/h           | 2.8 - 4.7         |
| Engine model          | -              | Develon<br>D24    |
| Power                 | hp/kW<br>@ rpm | 65/44.3<br>@ 2300 |
| Emission standard     | -              | Stage V           |
| Digging reach         | mm             | 6610              |
| Digging depth         | mm             | 4095              |
| Digging height        | mm             | 6025              |
| Length                | mm             | 5631              |
| Width                 | mm             | 1980              |
| Height                | mm             | 2575              |



## DX62R-7

6216

65/44.3  
@ 2300

0.175



## DX85R-7

9520

65/48.5 @ 2100

0.28

### DX63-7

6218

0.175

2.8 - 4.7

Develon  
D24

65/44.3  
@ 2300

Stage V

6440

4095

6025

5571

1980

2575

### DX85R-7

9520

0.28

2.7 - 4.7

Develon  
D24

65/48.5  
@ 2100

Stage V

7530

4665

7035

6265

2250

2657

# WHEELED EXCAVATORS



**DX57W-7      DX100W-7**

|                              |                |                  |               |
|------------------------------|----------------|------------------|---------------|
| <b>Operating weight</b>      | kg             | 5800             | 10700         |
| <b>Engine power</b>          | hp/kW @ rpm    | 52.3/42.5 @ 2400 | 100/75 @ 2000 |
| <b>Bucket capacity (SAE)</b> | m <sup>3</sup> | 0.175            | 0.3           |



**DX165WR-7K**



**DX170W-7K**

|                |                |
|----------------|----------------|
| 17400 - 18900  | 17700 - 19300  |
| 137/102 @ 2200 | 152/113 @ 2000 |
| 0.7            | 0.75           |

|                              |                | <b>DX57W-7</b>   | <b>DX100W-7</b> | <b>DX140W-7K</b> |
|------------------------------|----------------|------------------|-----------------|------------------|
| <b>Operating weight</b>      | kg             | 5800             | 10700           | 15800 - 17000    |
| <b>Bucket capacity (SAE)</b> | m <sup>3</sup> | 0.175            | 0.3             | 0.6              |
| <b>Travel speed</b>          | km/h           | 10 - 30          | 5.4 - 37.4      | 3.5 - 37         |
| <b>Engine model</b>          | -              | Develon D24      | Develon D34     | Develon DL06V    |
| <b>Power</b>                 | hp/kW @ rpm    | 52.3/42.5 @ 2400 | 100/75 @ 2000   | 152/113 @ 2000   |
| <b>Emission standard</b>     | -              | Stage V          | Stage V         | Stage V          |
| <b>Digging reach</b>         | mm             | 6108             | 7820            | 7585             |
| <b>Digging depth</b>         | mm             | 3495             | 4245            | 4490             |
| <b>Digging height</b>        | mm             | 5976             | 8265            | 8195             |
| <b>Length</b>                | mm             | 5896             | 5713            | 8043             |
| <b>Width</b>                 | mm             | 1947             | 2450            | 2495             |
| <b>Height</b>                | mm             | 2861             | 3011            | 3052             |
| <b>Arm length</b>            | mm             | 1600             | 2250            | 2100             |



## DX140W-7K

15800 - 17000

152/113 @2000

0.6



## DX160W-7K

17500 - 18100

152/113 @2000

0.7



## DX190W-7K

18320 - 20410

174/130 @ 1900

0.8



## DX210W-7K

21900 - 23000

189/141 @ 1900

0.9

## DX160W-7K DX165WR-7K DX170W-7K DX190W-7K DX210W-7K

| DX160W-7K         | DX165WR-7K        | DX170W-7K         | DX190W-7K         | DX210W-7K         |
|-------------------|-------------------|-------------------|-------------------|-------------------|
| 17500 - 18100     | 17400 - 18900     | 17700 - 19300     | 18320 - 20410     | 21900 - 23000     |
| 0.7               | 0.7               | 0.75              | 0.8               | 0.9               |
| 3.5 - 37          | 3 - 34            | 3.0 - 37          | 3.5 - 37          | 4.0 - 35          |
| Develon DL06V     | Perkins 1204J     | Develon DL06V     | Develon DL06V     | Develon DL06V     |
| 152/113<br>@ 2000 | 137/102<br>@ 2200 | 152/113<br>@ 2000 | 174/130<br>@ 1900 | 189/141<br>@ 1900 |
| Stage V           | Stage V           | Stage V           | Stage V           | Stage V           |
| 8235              | 8235              | 8875              | 9255              | 9980              |
| 5020              | 5020              | 5315              | 5725              | 6160              |
| 8850              | 8850              | 9140              | 9440              | 10140             |
| 8205              | 8205              | 8644              | 8867              | 9477              |
| 2495              | 2490              | 2530              | 2530              | 2495              |
| 3052              | 3102              | 3087              | 3131              | 3155              |
| 2500              | 2500              | 2500              | 2600              | 3000              |

# CRAWLER EXCAVATORS



DX140LCR-7    DX140LC-7

|                       |                |               |               |
|-----------------------|----------------|---------------|---------------|
| Operating weight      | kg             | 15500         | 14400         |
| Engine power          | hp/kW @ rpm    | 115/86 @ 2000 | 115/86 @ 2000 |
| Bucket capacity (SAE) | m <sup>3</sup> | 0.75          | 0.75          |



DX210LC-7    DX210NLC-7

|                |                |
|----------------|----------------|
| 21700          | 21700          |
| 166/124 @ 1800 | 166/124 @ 1800 |
| 1.2            | 1.2            |

DX140LCR-7    DX140LC-7    DX160LC-7HT

|                       |                |                |                |                |
|-----------------------|----------------|----------------|----------------|----------------|
| Operating weight      | kg             | 15500          | 14400          | 16800          |
| Bucket capacity (SAE) | m <sup>3</sup> | 0.75           | 0.75           | 0.8            |
| Travel speed          | km/h           | 2.9 - 4.7      | 2.9 - 4.7      | 2.3 - 3.7      |
| Engine model          | -              | Develon G2 D34 | Develon G2 D34 | Develon G2 D34 |
| Power                 | hp/kW @ rpm    | 115/86 @ 2000  | 115/86 @ 2000  | 115/86 @ 2000  |
| Emission standard     | -              | Stage V        | Stage V        | Stage V        |
| Digging reach         | mm             | 8285           | 8285           | 8285           |
| Digging depth         | mm             | 5485           | 5635           | 5635           |
| Digging height        | mm             | 9265           | 8660           | 8660           |
| Length                | mm             | 7360           | 7685           | 7685           |
| Width                 | mm             | 2590           | 2590           | 2590           |
| Height                | mm             | 2835           | 2785           | 2785           |
| Arm length            | mm             | 2500           | 2500           | 2500           |



## DX160LC-7HT

16800

115/86 @ 2000

0.8



## DX210-7

21300

166/124 @ 1800

1.1



## DX225LC-7 & 7X

23300

174/129 @ 1800

1.3



## DX235LC-7

23000

174/129 @ 1800

1.4

### DX210-7

### DX210LC-7

### DX210NLC-7

### DX225LC-7 & 7X

### DX235LC-7

21300

21700

21700

23300

23000

1.1

1.2

1.2

1.3

1.4

3.2 - 5.9

3.2 - 5.9

3.2 - 5.9

3.1 - 5.5

3.0 - 5.3

Develon DL06V Develon DL06V

Develon DL06V

Develon DL06V

Develon DL06V

166/124  
@ 1800

166/124  
@ 1800

166/124  
@ 1800

174/129  
@ 1800

174/129  
@ 1800

Stage V

Stage V

Stage V

Stage V

Stage V

9535

9535

9535

9865

9895

6270

6270

6270

6590

6595

9330

9330

9330

9620

9555

9445

9445

9445

9570

9522

2800

2990

2540

2990

2990

3139

3139

3139

3005

3139

2600

2600

2600

2900

2900

# CRAWLER EXCAVATORS



**DX235LCR-7    DX245NHD-7**

|                              |                |                |                |
|------------------------------|----------------|----------------|----------------|
| <b>Operating weight</b>      | kg             | 24300          | 25100          |
| <b>Engine power</b>          | hp/kW @ rpm    | 174/129 @ 1800 | 174/129 @ 1800 |
| <b>Bucket capacity (SAE)</b> | m <sup>3</sup> | 1.4            | 1.3            |



**DX350LC-7**

**DX380LC-7**

|  |                  |                |
|--|------------------|----------------|
|  | 36.100           | 40.200         |
|  | 285.6/213 @ 1800 | 326/240 @ 1800 |
|  | 1.85             | 2.0            |

**DX235LCR-7    DX245NHD-7    DX255LC-7**

|                              |                |                |                |                  |
|------------------------------|----------------|----------------|----------------|------------------|
| <b>Operating weight</b>      | kg             | 24300          | 25100          | 25700            |
| <b>Bucket capacity (SAE)</b> | m <sup>3</sup> | 1.4            | 1.3            | 1.5              |
| <b>Travel speed</b>          | km/h           | 3.2 - 5.8      | 3.0 - 5.3      | 3.2 - 5.6        |
| <b>Engine model</b>          | -              | Develon DL06V  | Develon DL06V  | Develon DL06V    |
| <b>Power</b>                 | hp/kW @ rpm    | 174/129 @ 1800 | 174/129 @ 1800 | 189/141.3 @ 1900 |
| <b>Emission standard</b>     | -              | Stage V        | Stage V        | Stage V          |
| <b>Digging reach</b>         | mm             | 9830           | 9465           | 10175            |
| <b>Digging depth</b>         | mm             | 6680           | 6095           | 6810             |
| <b>Digging height</b>        | mm             | 10805          | 9450           | 9705             |
| <b>Length</b>                | mm             | 8970           | 9566           | 10080            |
| <b>Width</b>                 | mm             | 2990           | 2540           | 3000 - 3200      |
| <b>Height</b>                | mm             | 3123           | 3190           | 3200             |
| <b>Arm length</b>            | mm             | 2900           | 2400           | 3000             |



### DX255LC-7

25700

189/141.3 @ 1900

1.5



### DX300LC-7

31500

271/202 @ 1800

1.7



### DX420LC-7

43500

344.4/257 @ 1800

2.2



### DX490LC-7

50400

394/294 @ 1800

3.0

| DX300LC-7         | DX350LC-7           | DX380LC-7         | DX420LC-7           | DX490LC-7                  |
|-------------------|---------------------|-------------------|---------------------|----------------------------|
| 31500             | 36.100              | 40.200            | 43500               | 50400                      |
| 1.7               | 1.85                | 2.0               | 2.2                 | 3.0                        |
| 3.0 - 5.5         | 3.5 - 5.7           | 3.0 - 5.4         | 3.2 - 5.3           | 3.2 - 5.6                  |
| Develon DL08V     | Develon DL08V       | Scania DC09       | Scania DC13         | Scania DC13                |
| 271/202<br>@ 1800 | 285.6/213<br>@ 1800 | 326/240<br>@ 1800 | 344.4/257<br>@ 1800 | 394/294<br>@ 1800          |
| Stage V           | Stage V             | Stage V           | Stage V             | Stage V                    |
| 10725             | 10980               | 11170             | 11430               | 12125                      |
| 7305              | 7540                | 7415              | 7635                | 7790                       |
| 10325             | 10325               | 10435             | 10615               | 11050                      |
| 10605             | 11350               | 11285             | 11740               | 12230                      |
| 3000 - 3200       | 3000 - 3280         | 3000 - 3350       | 3350                | 2990 - 3490<br>3340 - 3900 |
| 3050              | 3390                | 3415              | 3355                | 3350                       |
| 3100              | 3200                | 3200              | 3250                | 3350                       |

# CRAWLER EXCAVATORS



**DX530LC-7**

|                       |                |                |
|-----------------------|----------------|----------------|
| Operating weight      | kg             | 52900          |
| Engine power          | hp/kW @ rpm    | 394/294 @ 1800 |
| Bucket capacity (SAE) | m <sup>3</sup> | 3.3            |



**DX800LC-7**

|  |                |
|--|----------------|
|  | 79500          |
|  | 539/402 @ 2100 |
|  | 4.6            |



**DX1000LC-7**

|  |                |
|--|----------------|
|  | 99500          |
|  | 629/469 @ 2000 |
|  | 6.8            |

**DX530LC-7    DX800LC-7    DX1000LC-7**

|                       |                |                            |                |                |
|-----------------------|----------------|----------------------------|----------------|----------------|
| Operating weight      | kg             | 52900                      | 79500          | 99500          |
| Bucket capacity (SAE) | m <sup>3</sup> | 3.3                        | 4.6            | 6.8            |
| Travel speed          | km/h           | 3.2 - 5.6                  | 2.9 - 4.8      | 3.2 - 5.6      |
| Engine model          | -              | Scania DC13                | Perkins 2506   | Perkins 2806   |
| Power                 | hp/kW @ rpm    | 394/294 @ 1800             | 539/402 @ 2100 | 629/469 @ 2000 |
| Emission standard     | -              | Stage V                    | Stage V        | Stage V        |
| Digging reach         | mm             | 10735                      | 11250          | 12430          |
| Digging depth         | mm             | 6755                       | 6685           | 7260           |
| Digging height        | mm             | 9630                       | 10700          | 12425          |
| Length                | mm             | 11530                      | 12230          | 11530          |
| Width                 | mm             | 2990 - 3490<br>3340 - 3900 | 3400 - 4000    | 3440 - 4200    |
| Height                | mm             | 3350                       | 3540           | 3615           |
| Arm length            | mm             | 2900                       | 3350           | 2900           |

# WHEEL LOADERS



## DL200-7

|                              |                |                |
|------------------------------|----------------|----------------|
| <b>Operating weight</b>      | kg             | 12047          |
| <b>Engine power</b>          | hp/kW @ rpm    | 144/106 @ 2200 |
| <b>Bucket capacity (SAE)</b> | m <sup>3</sup> | 2.0            |



## DL220-7

|  |                |
|--|----------------|
|  | 13300          |
|  | 160/119 @ 2100 |
|  | 2.3            |



## DL250-7

|  |                |
|--|----------------|
|  | 13900          |
|  | 172/128 @ 2100 |
|  | 2.5            |

|                                                 |                | DL200-7        | DL220-7        | DL250-7        |
|-------------------------------------------------|----------------|----------------|----------------|----------------|
| <b>Operating weight</b>                         | kg             | 12047          | 13300          | 13900          |
| <b>Bucket range (GP)</b>                        | m <sup>3</sup> | 1.9 - 2.2      | 2.2 - 2.5      | 2.4 - 2.7      |
| <b>Engine model</b>                             | -              | Perkins 1204J  | Develon DL06   | Develon DL06   |
| <b>Power</b>                                    | hp/kW @ rpm    | 144/106 @ 2200 | 160/119 @ 2100 | 172/128 @ 2100 |
| <b>Emission standard</b>                        | -              | Stage V        | Stage V        | Stage V        |
| <b>Bucket capacity (SAE)</b>                    | m <sup>3</sup> | 2.0            | 2.3            | 2.5            |
| <b>Tipping load (straight/full turn at 40°)</b> | kg             | 10124/8933     | 10652/9383     | 11015/9696     |
| <b>Max. dump height on pivot</b>                | mm             | 3716           | 3853           | 3853           |
| <b>Breakout force</b>                           | kN             | 98             | 97             | 116            |
| <b>Maximum speed</b>                            | km/h           | 40             | 40             | 40             |
| <b>Turning radius at bucket</b>                 | mm             | 5414           | 6016           | 6115           |
| <b>Tires</b>                                    | -              | 20.5 R25       | 20.5 R25       | 20.5 R25       |
| <b>Length</b>                                   | mm             | 7208           | 7458           | 7487           |
| <b>Width - at tires edge</b>                    | mm             | 2539           | 2539           | 2539           |
| <b>Height</b>                                   | mm             | 3313           | 3313           | 3313           |

# WHEEL LOADERS



DL280-7

DL320-7

|                       |             |                |                |
|-----------------------|-------------|----------------|----------------|
| Operating weight      | kg          | 15562          | 19493          |
| Engine power          | hp/kW @ rpm | 190/141 @ 2000 | 271/202 @ 1800 |
| Bucket capacity (SAE) | m³          | 2.8            | 3.3            |



DL420CVT-7

DL480-7

|                |                |
|----------------|----------------|
| 23990          | 26444          |
| 326/240 @ 1800 | 345/257 @ 1800 |
| 4.5            | 4.8            |

|                                          |             | DL280-7        | DL320-7        | DL380-7        |
|------------------------------------------|-------------|----------------|----------------|----------------|
| Operating weight                         | kg          | 15562          | 19493          | 20269          |
| Bucket range (GP)                        | m³          | 2.7 - 3.1      | 3.3 - 3.8      | 3.7 - 4.1      |
| Engine model                             | -           | Develon DL06   | Develon DL08   | Develon DL08   |
| Power                                    | hp/kW @ rpm | 190/141 @ 2000 | 271/202 @ 1800 | 271/202 @ 1800 |
| Emission standard                        | -           | Stage V        | Stage V        | Stage V        |
| Bucket capacity (SAE)                    | m³          | 2.8            | 3.3            | 3.7            |
| Tipping load (straight/full turn at 40°) | kg          | 12247/10765    | 15948/14079    | 16248/14341    |
| Max. dump height on pivot                | mm          | 3934           | 4175           | 4175           |
| Breakout force                           | kN          | 140            | 170            | 181            |
| Maximum speed                            | km/h        | 40             | 40             | 40             |
| Turning radius at bucket                 | mm          | 6182           | 6748           | 6797           |
| Tires                                    | -           | 20.5 R25       | 23.5 R25       | 23.5 R25       |
| Length                                   | mm          | 7669           | 8530           | 8530           |
| Width – at tires edge                    | mm          | 2550           | 2845           | 2845           |
| Height                                   | mm          | 3360           | 3511           | 3511           |



### DL380-7

20269

271/202 @ 1800

3.9



### DL420-7

23990

345/257 @ 1800

4.5



### DL550-7

33209

380/283 @ 1800

5.4



### DL580-7

34311

400/294 @ 1800

6.0

| DL420-7 | DL420CVT-7 | DL480-7 | DL550-7 | DL580-7 |
|---------|------------|---------|---------|---------|
|---------|------------|---------|---------|---------|

23990

23990

26444

33209

34311

4.3 - 5.0

4.3 - 5.0

4.8 - 5.3

5.4 - 5.9

6.0 - 6.6

Scania DC13

Scania DC09

Scania DC13

Scania DC13

Scania DC13

345/257  
@ 1800

326/240  
@ 1800

345/257  
@ 1800

380/283  
@ 1800

400/294  
@ 1800

Stage V

Stage V

Stage V

Stage V

Stage V

4.3

4.3

4.8

5.4

6.0

19351/  
17071

19351/  
17071

20717/  
18282

24830/  
21897

27355/  
24315

4265

4265

4519

4806

4996

183

183

224

230

264

40

40

40

40

40

7065

7065

7352

7573

7596

26.5 R25

26.5 R25

26.5 R25

29.5 R25

29.5 R25

9138

9138

9454

9885

10059

2982

2982

2982

3289

3289

3660

3660

3635

3863

3863

# COMPACT WHEEL LOADERS



DL60-7

|                       |                |         |
|-----------------------|----------------|---------|
| Operating weight      | kg             | 3750    |
| Engine power          | hp/kW          | 66/48.5 |
| Bucket capacity (SAE) | m <sup>3</sup> | 0.6     |



DL80TL-7

|  |       |
|--|-------|
|  | 5200  |
|  | 75/55 |
|  | 0.9   |

|                                          |                | DL60-7         | DL65-7         |
|------------------------------------------|----------------|----------------|----------------|
| Operating weight                         | kg             | 3750           | 3650           |
| Bucket range (GP)                        | m <sup>3</sup> | 0.4 - 1.2      | 0.4 - 1.2      |
| Engine model                             | -              | Kubota V2403   | Kubota V2403   |
| Power                                    | hp/kW          | 66/48.5        | 66/48.5        |
| Emission standard                        | -              | Stage V        | Stage V        |
| Bucket capacity (SAE)                    | m <sup>3</sup> | 0.6            | 0.6            |
| Tipping load (straight/full turn at 40°) | kg             | 2160/1840      | 2325/1985      |
| Max. lifting height (pallet forks)       | mm             | 3290           | 2670           |
| Maximum speed                            | km/h           | 30             | 30             |
| Tires                                    | -              | 11.5/80 - 15.3 | 11.5/80 - 15.3 |
| Length                                   | mm             | 4660           | 4595           |
| Width – at tires edge                    | mm             | 1340           | 1340           |
| Height                                   | mm             | 2275           | 2275           |



### DL65-7

3650

66/48.5

0.6



### DL80-7

5200

75/55

0.9



### DL85-7

5100

75/55

0.9

### DL80-7

5200

0.6 - 2.0

Kubota V3307

75/55

Stage V

0.9

2965/2480

3500

20 - 35

11.5/80 - 15.3

5002

1460

2523

### DL80TL-7

5200

0.6 - 2.0

Kubota V3307

75/55

Stage V

0.9

2430/2050

4350

20 - 35

11.5/80 - 15.3

5310

1460

2523

### DL85-7

5100

0.6 - 2.0

Kubota V3307

75/55

Stage V

0.9

3220/2735

2850

20 - 35

11.5/80 - 15.3

4993

1460

2523

# ARTICULATED DUMP TRUCKS

|                                                 |                |
|-------------------------------------------------|----------------|
| Maximum payload                                 | kg             |
| Maximum power (ISO 3046)                        | kW @ rpm       |
| Body capacity heaped<br>(without/with tailgate) | m <sup>3</sup> |



## DA45-7

|            |
|------------|
| 41000      |
| 368 @ 2100 |
| 24.4/26.1  |

## DA30-7

|                                  |          |                                     |
|----------------------------------|----------|-------------------------------------|
| Speeds - forward                 | km/h     | 6 - 8 - 11 - 16 - 23 - 32 - 45 - 55 |
| Speeds - reverse                 | km/h     | 6 - 8 - 11 - 16                     |
| Engine model                     | -        | Scania DC9                          |
| Power                            | kW @ rpm | 276 @ 2100                          |
| Emission standard                | -        | Stage V                             |
| Transmission model               | -        | ZF 8 EP320                          |
| Weight empty<br>front/rear axle  | kg       | 12700/10500                         |
| Weight loaded<br>front/rear axle | kg       | 15872/35328                         |
| Net weight                       | kg       | 23200                               |
| Length                           | mm       | 9534                                |
| Width                            | mm       | 2967                                |
| Total height                     | mm       | 3560                                |



## DA30-7

28000

276 @ 2100

16.8/17.8



## DA45-7 4X4

41000

368 @ 2100

25.7

### DA45-7

### DA45-7 4X4

5 - 8 - 11 - 16 - 23 - 32 - 45 - 55

5 - 8 - 11 - 16 - 23 - 32 - 45 - 55

5 - 8 - 11 - 16

5 - 8 - 11 - 16

Scania DC13

Scania DC13

368 @ 2100

368 @ 2100

Stage V

Stage V

ZF 8 EP420

ZF 8 EP420

14200/15900

14500/16000

22041/49059

22165/49335

30100

30500

10590

10187

3475

3990

3850

3850

# SLR MACHINES



## SLR and Semi-SLR

## DX225LC-7 SLR

|                       |                |                |
|-----------------------|----------------|----------------|
| Operating weight      | kg             | 24600          |
| Bucket capacity (SAE) | m <sup>3</sup> | 0.45           |
| Travel speed          | km/h           | 3.1 - 5.5      |
| Engine model          | -              | Develon DL06V  |
| Power                 | hp/kW @ rpm    | 174/129 @ 1800 |
| Emission standard     | -              | Stage V        |
| Digging reach         | mm             | 15365          |
| Digging depth         | mm             | 11660          |
| Digging height        | mm             | 13045          |
| Length                | mm             | 12390          |
| Width                 | mm             | 3190           |
| Height                | mm             | 3385           |



| <b>DX300LC-7 SLR</b> | <b>DX530LC-7 Semi SLR</b> | <b>DX530LC-7 SLR</b> |
|----------------------|---------------------------|----------------------|
| 33000                | 51900                     | 52200                |
| 0.64                 | 1.27                      | 0.92                 |
| 3.0 - 5.5            | 3.2 - 5.6                 | 3.2 - 5.6            |
| Develon DL08P        | Scania DC13               | Scania DC13          |
| 271/202<br>@ 1800    | 394/294<br>@ 1800         | 394/294<br>@ 1800    |
| Stage V              | Stage V                   | Stage V              |
| 17510                | 16060                     | 19615                |
| 13780                | 11795                     | 15125                |
| 14195                | 12755                     | 14435                |
| 14320                | 14155                     | 16195                |
| 3400                 | 3340 - 3900               | 3340 - 3900          |
| 3475                 | 3910                      | 4070                 |

# MATERIAL HANDLING MACHINES



## Material Handling Machines

## DX270WHM-7 Straight Arm

|                    |             |                |
|--------------------|-------------|----------------|
| Arm configuration  |             | Straight       |
| Operating weight   | kg          | 28300          |
| Travel speed       | km/h        | 4 / 9 / 20     |
| Engine model       | -           | Develon DL06V  |
| Power (SAE J1995)  | hp/kW @ rpm | 189/141 @ 1900 |
| Emission standard  | -           | Stage V        |
| Max. pin height    | mm          | 12775          |
| Max. working reach | mm          | 11155          |
| Max. working depth | mm          | 4270           |
| Boom length        | mm          | 6,6            |
| Arm length         | mm          | 4,5            |
| Min. swing radius  | mm          | 2855           |
| Elevating height   | mm          | 2600           |



## Material Handling Machines

## DX270WHM-7 Gooseneck Arm

| Arm configuration  |             | Gooseneck      | Long gooseneck |
|--------------------|-------------|----------------|----------------|
| Operating weight   | kg          | 28100          | 28700          |
| Travel speed       | km/h        | 4 / 9 / 20     | 4 / 9 / 20     |
| Engine model       | -           | Develon DL06V  | Develon DL06V  |
| Power (SAE J1995)  | hp/kW @ rpm | 189/141 @ 1900 | 189/141 @ 1900 |
| Emission standard  | -           | Stage V        | Stage V        |
| Max. pin height    | mm          | 12955          | 13830          |
| Max. working reach | mm          | 11525          | 12410          |
| Max. working depth | mm          | 4830           | 5355           |
| Boom length        | mm          | 6,6            | 7,1            |
| Arm length         | mm          | 5              | 5,4            |
| Min. swing radius  | mm          | 2855           | 2855           |
| Elevating height   | mm          | 2600           | 2600           |

# TUNNELING MACHINES



## Tunneling Machines

## DX235RTF-7

|                    |               |                |
|--------------------|---------------|----------------|
| Operating weight   | kg            | 25689          |
| Boom tilting angle | °             | 2 x 45         |
| Travel speed       | km/h          | 3,2 - 5,8      |
| Engine model       | Develon DL06V |                |
| Power              | hp/kW @ rpm   | 189/141 @ 1900 |
| Emission standard  | Stage V       |                |
| Digging reach      | mm            | 9260           |
| Digging depth      | mm            | 5130           |
| Digging height     | mm            | 9900           |
| Length             | mm            | 9750           |
| Width              | mm            | 2990           |
| Height             | mm            | 3080           |



## DX140RDM-7

| Configuration                |                | Monolithic HRD | Interchangeable HRD | Interchangeable Digging |
|------------------------------|----------------|----------------|---------------------|-------------------------|
| Operating weight             | kg             | 22500          | 23100               | 22100                   |
| Travel speed                 | km/h           | 2,9 - 4,7      | 2,9 - 4,7           | 2,9 - 4,7               |
| Engine model                 | -              | Develon G2 D34 | Develon G2 D34      | Develon G2 D34          |
| Power SAE J1995              | hp/kW @ rpm    | 115/86 @ 1800  | 115/86 @ 1800       | 115/86 @ 1800           |
| Emission standard            | -              | Stage V        | Stage V             | Stage V                 |
| Number of cylinders          | -              | 4              | 4                   | 4                       |
| Pin height                   | mm             | 16100          | 16100               | -                       |
| Max tool weight              | kg             | 1450 kg        | 1250 kg             | -                       |
| Max GP Bucket                | m <sup>3</sup> | -              | -                   | 0.76                    |
| Track length                 | mm             | 4130           | 4130                | 4130                    |
| Transport width              | mm             | 2590           | 2590                | 2590                    |
| Variable undercarriage width | mm             | 2540-3740      | 2540-3740           | 2540-3740               |
| Overall height               | mm             | 3020           | 3020                | 3020                    |
| Shoe width                   | mm             | 500            | 500                 | 500                     |

# DEMOLITION MACHINES



| Demolition Machines          |             | DX245DM-7      | DX245DM-7      |
|------------------------------|-------------|----------------|----------------|
| Configuration                |             | HRD            | Digging        |
| Operating weight             | kg          | 30800          | 28900          |
| Travel speed                 | km/h        | 3.0 - 5.5      | 3.0 - 5.5      |
| Engine model                 | -           | Develon DL06P  | Develon DL06P  |
| Power (SAE J1995)            | hp/kW @ rpm | 173/129 @ 1800 | 173/129 @ 1800 |
| Emission standard            | -           | Stage V        | Stage V        |
| Pin reach                    | mm          | 12900          | 8170           |
| Pin depth                    | mm          | N/A            | 4785           |
| Pin height                   | mm          | 18070          | 8155           |
| Overall length               | mm          | 11460          | 9590           |
| Width superstructure         | mm          | 2540           | 2540           |
| Variable undercarriage width | mm          | 2540 ~ 3740    | 2540 ~ 3740    |
| Overall height               | mm          | 3150           | 3150           |



### DX380DM-7

### DX380DM-7

| Configuration                |                | HRD               | Digging           |
|------------------------------|----------------|-------------------|-------------------|
| Operating weight             | kg             | 47400             | 44800             |
| Travel speed                 | km/h           | 3.0 - 5.4         | 3.0 - 5.4         |
| Engine model                 | -              | Scania DC09       | Scania DC09       |
| Power (SAE J1995)            | hp/kW<br>@ rpm | 327/240<br>@ 1800 | 327/240<br>@ 1800 |
| Emission standard            | -              | Stage V           | Stage V           |
| Pin reach                    | mm             | 14500             | 10200             |
| Pin depth                    | mm             | N/A               | 5500              |
| Pin height                   | mm             | 23000             | 9200              |
| Overall length               | mm             | 15200             | 11285             |
| Width superstructure         | mm             | 2990              | 2990              |
| Variable undercarriage width | mm             | 2970 ~ 4370       | 2970 ~ 4370       |
| Overall height               | mm             | 3148              | 3148              |

# DEMOLITION MACHINES



| Demolition Machines          |             | DX530DM-7      | DX530DM-7      |
|------------------------------|-------------|----------------|----------------|
| Configuration                |             | HRD            | Digging        |
| Operating weight             | kg          | 60500          | 56800          |
| Travel speed                 | km/h        | 3.1 - 5.5      | 3.1 - 5.5      |
| Engine model                 | -           | Scania DC13    | Scania DC13    |
| Power (SAE J1995)            | hp/kW @ rpm | 394/294 @ 1800 | 394/294 @ 1800 |
| Emission standard            | -           | Stage V        | Stage V        |
| Pin reach                    | mm          | 16500          | 10300          |
| Pin depth                    | mm          | N/A            | 5965           |
| Pin height                   | mm          | 27500          | 9690           |
| Length                       | mm          | 18500          | 12230          |
| Width                        | mm          | 2990           | 2990           |
| Variable undercarriage width | mm          | 2970 ~ 4370    | 2970 ~ 4370    |
| Height                       | mm          | 3360           | 3360           |



### DX530DM-7

### DX530DM-7

| Configuration                |                | HRD               | Digging           |
|------------------------------|----------------|-------------------|-------------------|
| Operating weight             | kg             | 70500             | 63000             |
| Travel speed                 | km/h           | 3.1 - 5.5         | 3.1 - 5.5         |
| Engine model                 | -              | Scania DC13       | Scania DC13       |
| Power (SAE J1995)            | hp/kW<br>@ rpm | 394/294<br>@ 1800 | 394/294<br>@ 1800 |
| Emission standard            | -              | Stage V           | Stage V           |
| Pin reach                    | mm             | 18000             | 10300             |
| Pin depth                    | mm             | N/A               | 5965              |
| Pin height                   | mm             | 31000             | 9690              |
| Length                       | mm             | 22300             | 12230             |
| Width                        | mm             | 2990              | 2990              |
| Variable undercarriage width | mm             | 2970 ~ 4370       | 2970 ~ 4370       |
| Height                       | mm             | 3360              | 3360              |

# DOZER



| Model                                    |                      | DD130          |
|------------------------------------------|----------------------|----------------|
| Operating weight                         | kg                   | 14.500         |
| Engine power                             | hp/kW<br>@ rpm       | 157/117 @2200  |
| Max. traction force                      | t                    | 22             |
|                                          |                      |                |
| Travelling Performance, Travelling Speed | km/h                 | 9              |
| Overall lenght with blade & Ripper       | mm                   | 6030           |
| Overall lenght with blade only           | mm                   | 5035           |
| Overall width (Blades width)             | mm<br>(XL/LGP1/LGP2) | 3105/3345/3655 |
| XL-Version with 560-mm-shoes             | cm2                  | 33818          |
| LGP1-Version with 710-mm-shoes           | cm2                  | 42875          |
| LGP2-Version with 760-mm-shoes           | cm2                  | 45895          |

# ATTACHMENTS


## DO IT ALL!

Range of Develon Buckets, Breakers, Quick Couplers, Pallet Forks and more...

For: Develon wheel loaders, crawler and wheeled excavators.



DISCOVER MORE:



HD Hyundai Infracore Europe, s.r.o.  
IBC - Pobřežní 620/3, 186 00 Praha 8-Karlín  
Czech Republic

©2025 DEVELON D4600683-EN (03/25)

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice.

Specification(s) for your individual Develon equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of Develon units may show other than standard equipment.

# DEVELON